

RADIFORM

Quality Certified Components

Product:

Cable Ties – CT Commercial grade nylon 6/6

Applications:

Securing hoses, cables, poles and pipes etc for internal environments.

General:

- One piece injection moulded
- Flame retardant to comply with UL94V-2
- Halogen free
- Operating temperature -40°C to 85°C

Specifications:

Products are UL Listed to Standard UL62275 File E 469183

Material Nylon 6/6

Cat. No.	Dimensions mm		Bundle Diameter mm		Loop Tensile Strength	
	Length	Width	Min.	Max.	N	kg
CT100-2.5-BK	100	2.5	3	20.5	80	8
CT150-3.2-BK	150	3.2	3	36	180	18
CT200-4.8-BK	200	4.8	3	49.5	220	22
CT200-7.6-BK	200	7.6	6	49.5	550	55
CT300-4.8-BK	300	4.8	3	81	220	22
CT370-4.8-BK	370	4.8	3	103.5	220	22
CT370-7.6-BK	370	7.6	6	103.5	550	55
CT550-7.6-BK	550	7.6	9	162.5	1200	120
CT750-8.8-BK	750	8.8	9	229.5	1200	120
CT100-2.5-NT	100	2.5	3	20.5	80	8
CT150-3.2-NT	150	3.2	3	36	180	18
CT200-4.8-NT	200	4.8	3	49.5	220	22
CT300-4.8-NT	300	4.8	3	81	220	22
CT370-4.8-NT	370	4.8	3	103.5	220	22
CT370-7.6-NT	370	7.6	6	103.5	550	55
CT750-8.8-NT	750	8.8	9	229.5	1200	120

*All catalogue numbers ending in BK are black in colour, those ending in NT are natural nylon.

The above information corresponds to our actual knowledge and are according to our knowledge is rendered correct and reliable. But they do not represent binding properties. Customers and end-users need to decide autonomously about the application of the product in the provided range. Under no circumstances is Red2Go Pty Ltd liable for any eventual, indirect or consequential damages arising from the sales, resale, transfer, use or misuse of the product. Our Liabilities are limited to only in replacing products due to any unforeseen specification variance.