

# **RADIFORM**

**Quality Certified Components**

**Product:**

**Cable Ties – CTUV Ascend Vydyne and Nylon 6/6**

**Applications:**

Securing hoses, cables, poles and pipes etc in outdoor environments.

**General:**

- UV endurance beyond 7 years outdoors
- One piece injection moulded
- Flame retardant to comply with UL94V-2
- Halogen free
- Operating temperature -40°C to 85°C

**Specifications:**

Products are UL Listed to Standard UL62275 File E 469183

Material Used: Dupont Zytel 145BK or Ascend Vydyne 25WSP

Cat. No.	Dimensions mm		Bundle Diameter mm		Loop Tensile Strength	
	Length	Width	Min.	Max.	N	kg
CTUV100-2.5	100	2.5	3	20.5	80	8
CTUV150-3.6	150	3.6	3	36	180	18
CTUV200-4.8	200	4.8	3	49.5	220	22
CTUV200-7.6	200	7.6	6	50.9	550	55
CTUV300-4.8	300	4.8	3	81	220	22
CTUV300-7.6	300	7.6	3	82.8	550	55
CTUV370-4.8	370	4.8	6	103.5	220	22
CTUV370-7.6	370	7.6	6	103.5	550	55
CTUV530-12.4	530	12.4	9	156	1200	120
CTUV550-7.6	550	7.6	6	162.5	550	55
CTUV650-12.4	650	12.4	9	195	1200	120
CTUV750-8.8	750	8.8	9	229.5	800	80
CTUV1220-9	1220	9	9	375.5	800	80

\*All CTUV cable ties are Black in colour

The above information corresponds to our actual knowledge and are according to our knowledge is rendered correct and reliable. But they do not represent binding properties. Customers and end-users need to decide autonomously about the application of the product in the provided range. Under no circumstances is Red2Go Pty Ltd liable for any eventual, indirect or consequential damages arising from the sales, resale, transfer, use or misuse of the product. Our Liabilities are limited to only in replacing products due to any unforeseen specification variance.