

# **RADIFORM**

**Quality Certified Components**

**Product:**

**Cable Ties – SST 316 Stainless Steel Natural or Polyester Coated**

**Applications:**

Securing hoses, cables, poles and pipes etc in harsh environments.

**General:**

- Smooth rounded edges help ensure safe handling
- Self locking ball speeds installation
- Polyester coated types comply with UL94V-2 and are halogen free
- Polyester types are resistant to UV

**Specifications:**

Products are UL Listed to Standard UL62275 File E 469183

Cat. No.	Bundle Diameter mm		Loop Tensile Strength		Operating Temperature °C	
	Min.	Max.	N	kg	Min	Max
SST125	15	25	890	90	-60	300
SST200	15	50	890	90	-60	300
SST200C	15	50	450	45	-40	85
SST360	15	102	890	90	-60	300
SST360C	15	102	450	45	-40	85
SST360HD	15	102	1500	158	-60	300
SST360HDC	15	102	800	79	-40	85
SST520HD	15	152	1500	158	-60	300
SST520HDC	15	152	800	79	-40	85

\*Catalogue numbers ending in C denote Polyester Coated.

The above information corresponds to our actual knowledge and are according to our knowledge is rendered correct and reliable. But they do not represent binding properties. Customers and end-users need to decide autonomously about the application of the product in the provided range. Under no circumstances is Red2Go Pty Ltd liable for any eventual, indirect or consequential damages arising from the sales, resale, transfer, use or misuse of the product. Our Liabilities are limited to only in replacing products due to any unforeseen specification variance.