

**Product:**

**Heat Shrink – HSPK Submersible Pump Kits**

**Applications:**

Designed to accommodate the flat ribbon cable from submersible pumps to circular cable. Two kits are available to cover 1mm<sup>2</sup> through to 6mm<sup>2</sup> conductors in up to four core cables.

**General:**

- Resistance to copper corrosion and fungus
- Hot melt adhesive for effective water and environmental sealing
- High shrink ratio tubes
- Rated to 600VAC

**Kit Contents:**

- 4 x tinned copper splice connectors
- 4 x RDW dual wall heat shrink pieces
- A length of RMW medium wall heat shrink
- Preparation sand paper
- Instructions

**Specifications:**

<b>Product Technical Data</b>	
<b>Component</b>	<b>Specification</b>
Copper Splice	99.9% Purity Copper. Annealed & tinned
RDW Heat Shrink	IEC, ASTM
RMW Heat Shrink	IEC, ASTM, BS6910-1

The above information corresponds to our actual knowledge and are according to our knowledge is rendered correct and reliable. But they do not represent binding properties. Customers and end-users need to decide autonomously about the application of the product in the provided range. Under no circumstances is Red2Go Pty Ltd liable for any eventual, indirect or consequential damages arising from the sales, resale, transfer, use or misuse of the product. Our Liabilities are limited to only in replacing products due to any unforeseen specification variance.